

# NEO



## Scan. Connect. Communicate.

Psion Teklogix listens to our customers. When you challenged us to deliver an entry level handheld that is rugged, flexible, ergonomic and meets the demands of light industrial, retail, or supply chain logistics operations, we delivered NEO.

NEO delivers performance and durability packaged in a superior ergonomic design. An innovative easy to read, tilted display provides the right balance of styling and comfort for extended hours of use and delivers optimal viewing during data capture. With its unique expansion options, NEO provides maximum investment protection allowing you to meet your current and evolving application needs.



### Features & Benefits

#### Innovative, Ergonomic Design

- Class leading ergonomics provide superior ease of use
- Unique, tilted display provides optimal viewing during data capture and ensures comfort
- Compact enough to fit in a pocket

#### Robust Built-In Functionality

- Microsoft Windows® CE.NET based mobile handheld computer with integrated data capture and communications
- Supports WLAN with Push-To-Talk technology and Bluetooth®
- 2.7" bright, colour touch screen display delivers incredible readability both indoors and outdoors
- Integrated imager/scanner allows for data capture
- Expansion capability delivers flexibility to incorporate new technologies for future application needs (i.e.: RFID) and provides investment protection

#### Essential Ruggedness

- Rugged design and durability delivers maximum up-time and increased productivity
- Withstands 26 drops from 1.2 meters (4 ft) to polished concrete
- Includes IP54 rating, protecting against dust and water
- Operating temperature range of -10°C to +50°C (14°F to 122°F)

#### Typical Applications

- Front Store Retail: Mobile stock checking, price checking, merchandising
- Light Duty Warehousing: Inventory tracking, stocking, back-dock shipping and receiving
- Utilities: Meter reading, surveying, parking enforcement, asset tracking
- Courier/Parcel Delivery
- Ticket Verification: theatre and sporting events



## Specifications\*

### MODEL VARIANTS

#### Batch

2.7" Colour Touch Screen, Numeric Keypad, Windows® CE 5.0 Core, 64/128 MB Memory, Micro SD Slot, 3000 mAh Battery

#### Plus Batch Options:

- Bluetooth® Radio
- Bluetooth® Radio and ID Imager
- Bluetooth® Radio and ID Laser Scanner

#### Connected

2.7" Colour Touch Screen, Windows® CE 5.0 Professional, 64/128 MB Memory, Micro SD Slot, 3000 mAh Battery, VoIP (Push-To-Talk), WiFi/BT Radio

#### Plus Connected Options:

- ID Imager
- ID Laser Scanner

*The connected variant is available in 2 keypad configurations (26 Key Numeric or 48 Key Alpha – Numeric)*

### PLATFORM

#### Processor

- PXA270 Processor @ 312 Mhz

#### Memory

- On-board RAM: 128 MB SDRAM
- On-board ROM: 64 MB Flash

### OPERATING SYSTEM

- Microsoft® Windows® CE 5.0

### PROGRAMMING ENVIRONMENT

- HTML, XML
- Mobile Devices SDK
  - HTML, XML
  - Java™
  - Visual Studio® 2008
  - Standard protocol APIs – Windows® sockets (WinCE)

### WIRELESS COMMUNICATIONS

- On-board IEEE 802.11b/g (CCX Certified)
- On-board Bluetooth® radio (10 m range)

### APPLICATION SOFTWARE

- Internet Explorer® 6 for CE
- Wordpad
- Active Sync
- Open TekTerm
- ANSI
- TESS terminal emulations
- IBM 3270, IBM 5250, HP 2392
- Wavelink®
- MCL
- MCC
- PTX Connect

### BARCODE APPLICATIONS

- ID Standard Laser Scanner Option
- ID Standard Imager Option

### USER INTERFACE

- Multicolour LED for scanning and charging

#### Display (Backlit)

- 2.7 in QVGA portrait mode
- QWERTY virtual option
- Sunlight readable transmissive with touch screen
- Colour 240 x 320 graphic TFT
- Passive stylus or finger operation

#### Keypad (Backlit)

- 48 key Alpha Numeric
- 26 large key Numeric
- LED backlit keypad
- Ergonomically enhanced for ambidextrous one-hand operation

#### Audio

- Built-in microphone and receiver on all "Connected" variants
- 85 db internal beeper
- Bluetooth® (on equipped models)

### INTERNAL EXPANSION SLOTS

- One MicroSD slot

### EXPANSION PORT

- Battery Power
- USB signaling

### DOCKING PORT

- RS232
- USB
- DC Input

### POWER MANAGEMENT

- 3.7V @ 3000 mAh Li-ion rechargeable battery
- 8 hour battery operation
- Smart battery system
- Built in gas gauge & performance monitor
- System backup (up to 10 minutes) during battery swap
- 3 day real time clock backup
- Adjustable battery allocation between system backup and runtime

### USER ENVIRONMENT

- Operating Temperature:
  - 10°C to +50°C (14°F to 122 °F)
- Storage Temperature:
  - 20°C to +60°C (13°F to 140°F)
- Relative Humidity: 5% to 95% RH non-condensing
- Rain & Dust Protection: IP54, IEC 529
- Drop: 1.2m (4 ft) – 26 drops to polished concrete
- Shock and Vibe: Random vibration 5 m2/s3 @ 10 to 100 Hz, 1 m2/s3 @ 200-2000 with duration of 30 min/axes, 3 axes, and shock of 300 m/s2 @ 11ms and 1000 m/s2 @ 6ms
- ESD: +/- 8k Vdc air discharge, +/- 4k Vdc contacts

### PHYSICAL DIMENSIONS AND WEIGHT

- Device: 168 mm x 64 mm x 34 mm / (6.6" x 2.5" x 1.3")
- Grip Area: 56 mm / 2.2" (W)
- Weight with battery: 275 g (0.6 lb)

### ACCESSORIES

- Desk Top Charger
- Quad Unit Charger
- Pistol Grip
- Additional miscellaneous adaptors and cables
- Carrying Accessories  
*(a complete list of accessories is available at [www.psoneteklogix.com](http://www.psoneteklogix.com))*

### REGULATORY APPROVALS

- FCC 15.247
- IC RSS210
- CE ETSI EN 300 328, ETSI EN 301 489, EN 55022, EN55024
- Safety IEC 60950-1
- Laser Safety IEC 60825-1

Product is ROHS Compliant



\*Specifications are subject to change without notice.

[www.psoneteklogix.com](http://www.psoneteklogix.com)



Pson Teklogix™ is a trademark of Pson Teklogix Inc. Other product names mentioned in this document may be trademarks of Pson Teklogix Inc. or trademarks or registered trademarks of other hardware, software, or service providers and are used herein for identification purposes only.

Windows and the Windows Logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries.